

## Panels raised and fielded - 15 mm MDF without polystyrene

**Construction:**

15 mm MDF ( Appr.720 kg/m<sup>3</sup> - heat conductivity: 0,13 W/mK )  
 Meets the standards of "Symbol H" - cf. DS/EN 316 and DS/EN 622-5 concerning MDF sheets

**U-Value:**

| U-Value - W/m <sup>2</sup> K |  |
|------------------------------|--|
| 15 mm                        |  |
| 3,53                         |  |

Heat conductivity is calculated on the basis of the practical heat conductivity of each included material - taken from data sheets and DS418, version 6, 2002. Also relating to EN 12524.

**Weight:**

| Weight appr. Kg./m <sup>2</sup> |  |
|---------------------------------|--|
| 15 mm                           |  |
| 10,8                            |  |

**Measure:**

Min.: 120 x 250 mm - Max.: 1200 x 2400 mm

**Tolerances:**


Width/Height: +/- 1 mm - Diagonal: +/- 1,5 mm - Thickness: +/- 0,8 mm

**Section drawing:**

Profile type 1




Profile type 2



Profile type 3



Profile type 4



|                |                 |            |
|----------------|-----------------|------------|
| Made: 10.03.14 | Data sheet: PMN | Draw.: HMN |
| Revised:       | Data sheet:     | Draw.:     |

O.H.Industri A/S  
 Smedevej 17  
 DK - 7430 Ikast  
 +45 9725 1200  
[www.ohindustri.com](http://www.ohindustri.com)